

IMAGE PROCESSING APPARATUS, IMAGE PROCESSING METHOD
AND RECORDING MEDIUM

BACKGROUND OF THE INVENTION

5 Field of the Invention

The present invention relates to image processing apparatus and method having a new function, and a recording medium storing a program to achieve the above method.

10 Related Background Art

Conventionally, an image processing apparatus such as a TV set or the like has various image quality adjustment functions related to hue, chromaticity, contrast, lightness and the like on a displayed image.

15 However, in the image quality adjustment in this kind of conventional image processing apparatus, it is hard to objectively know effect, difference or the like in the adjustment, therefore, there is a problem that it is hard to judge whether or not the optimum
20 adjustment was performed.

SUMMARY OF THE INVENTION

The present invention is made in consideration of the above-mentioned problem, and an object thereof is
25 to provide convenience in performing image quality adjustment by simultaneously displaying a preadjustment image, a default adjustment image and an adjustment

2004221 01102

image when the image quality adjustment such as adjustment of contrast, color balance or the like is performed in an image processing apparatus.

To achieve the above object, the invention
5 according to a first aspect is characterized by an image processing apparatus comprising: a multiscreen synthesis means for composing one screen by executing a trimming process to a part of an input image and arranging plural pieces of that image; an image quality
10 adjustment value storage means for storing image quality adjustment values for plural kinds of image quality adjustment processes; an image quality adjustment process means for executing the image quality adjustment processes for plural images on the
15 basis of the image quality adjustment values stored in the image quality adjustment value storage means; and a control means for converting an input image into a first image to which an image quality adjustment process was executed by the image quality adjustment
20 process means on the basis of an image quality adjustment value before performing an image quality adjustment operation stored in the image quality adjustment value storage means, and similarly converting the input image into a second image to which
25 an image quality adjustment process was executed by the image quality adjustment process means on the basis of an image quality adjustment value of newly performing

an adjustment operation, then displaying these converted first and second images on one screen with arranged state by the multiscreen synthesis means.

To achieve the above object, the invention according to a second aspect is characterized by an image processing apparatus comprising: an image enlargement and reduction means for enlarging and reducing an input image; a multiscreen synthesis means for composing one screen by arranging plural pieces of the input image reduced by the image enlargement and reduction means; an image quality adjustment value storage means for storing image quality adjustment values for plural kinds of image quality adjustment processes; an image quality adjustment process means for executing the image quality adjustment processes for plural images on the basis of the image quality adjustment values stored in the image quality adjustment value storage means; and a control means for executing an image quality adjustment process to an input image by the image quality adjustment process means on the basis of an image quality adjustment value before performing an image quality adjustment operation stored in the image quality adjustment value storage means and converting the input image into a first image which was reduced by the image enlargement and reduction means, and similarly executing an image quality adjustment process to the input image by the

20110101 011102

image quality adjustment process means on the basis of
an image quality adjustment value of newly performing
an adjustment operation and converting the input image
into a second image which was reduced by the image
5 enlargement and reduction means, then displaying these
converted first and second images on one screen with
arranged state by the multiscreen synthesis means.

To achieve the above object, the invention
according to a third aspect is characterized by an
10 image processing apparatus comprising: an image
enlargement and reduction means for enlarging and
reducing an input image; a multiscreen synthesis means
for composing one screen by executing a trimming
process to a part of the image reduced by the image
15 enlargement and reduction means and arranging plural
pieces of that image; an image quality adjustment value
storage means for storing image quality adjustment
values for plural kinds of image quality adjustment
processes; an image quality adjustment process means
20 for executing the image quality adjustment processes
for plural images on the basis of each of combinations
of the image quality adjustment values stored in the
image quality adjustment value storage means; and a
control means for executing an image quality adjustment
25 process to an input image by the image quality
adjustment process means on the basis of an image
quality adjustment value before performing an image

4004234 "0110"

quality adjustment operation stored in the image
quality adjustment value storage means and converting
the input image into a first image which was reduced by
the image enlargement and reduction means, and
5 similarly executing an image quality adjustment process
to the input image by the image quality adjustment
process means on the basis of an image quality
adjustment value of newly performing an adjustment
operation and converting the input image into a second
10 image which was reduced by the image enlargement and
reduction means, then displaying these converted first
and second images on one screen with arranged state by
the multiscreen synthesis means.

To achieve the above object, the invention
15 according to a fourth aspect is characterized by an
image processing method comprising: a multiscreen
synthesis step of composing one screen by executing a
trimming process to a part of an input image and
arranging plural pieces of that image; an image quality
20 adjustment value storage step of storing image quality
adjustment values for plural kinds of image quality
adjustment processes; and an image quality adjustment
process step of executing the image quality adjustment
processes for plural images on the basis of each of
25 combinations of the image quality adjustment values
stored in the image quality adjustment value storage
step, wherein an input image is converted into a first

image to which an image quality adjustment process was
executed in the image quality adjustment process step
on the basis of an image quality adjustment value
before performing an image quality adjustment operation
5 stored in the image quality adjustment value storage
step, and similarly the input image is converted into a
second image to which an image quality adjustment
process was executed in the image quality adjustment
process step on the basis of an image quality
10 adjustment value of newly performing an adjustment
operation, then these converted first and second images
are displayed on one screen with arranged state in the
multiscreen synthesis step.

To achieve the above object, the invention
15 according to a fifth aspect is characterized by an
image processing method comprising: an image
enlargement and reduction step of enlarging and
reducing an input image; a multiscreen synthesis step
of composing one screen by arranging plural pieces of
20 the input image reduced in the image enlargement and
reduction step; an image quality adjustment value
storage step of storing image quality adjustment values
for plural kinds of image quality adjustment processes;
and an image quality adjustment process step of
25 executing the image quality adjustment processes for
plural images on the basis of each of combinations of
the image quality adjustment values stored in the image

quality adjustment value storage step, wherein an image
quality adjustment process is executed to an input
image in the image quality adjustment process step on
the basis of an image quality adjustment value before
5 performing an image quality adjustment operation stored
in the image quality adjustment value storage step and
the input image is converted into a first image which
was reduced in the image enlargement and reduction
step, and similarly an image quality adjustment process
10 is executed to the input image in the image quality
adjustment process step on the basis of an image
quality adjustment value of newly performing an
adjustment operation and the input image is converted
into a second image which was reduced in the image
15 enlargement and reduction step, then these converted
first and second images are displayed on one screen
with arranged state in the multiscreen synthesis step.

To achieve the above object, the invention
according to a sixth aspect is characterized by an
20 image processing method comprising: an image
enlargement and reduction step of enlarging and
reducing an input image; a multiscreen synthesis step
of composing one screen by executing a trimming process
to a part of the image reduced in the image enlargement
25 and reduction step and arranging plural pieces of that
image; an image quality adjustment value storage step
of storing image quality adjustment values for plural

10042231.01102

1 kinds of image quality adjustment processes; and an
image quality adjustment process step of executing the
image quality adjustment processes for plural images on
the basis of each of combinations of the image quality
5 adjustment values stored in the image quality
adjustment value storage step, wherein an image quality
adjustment process is executed to an input image in the
image quality adjustment process step on the basis of
an image quality adjustment value before performing an
10 image quality adjustment operation stored in the image
quality adjustment value storage step and the input
image is converted into a first image which was reduced
in the image enlargement and reduction step, and
similarly an image quality adjustment process is
15 executed to the input image in the image quality
adjustment process step on the basis of an image
quality adjustment value of newly performing an
adjustment operation and the input image is converted
into a second image which was reduced in the image
20 enlargement and reduction step, then these converted
first and second images are displayed on one screen
with arranged state in the multiscreen synthesis step.

To achieve the above object, the invention
according to a seventh aspect is characterized by a
25 recording medium which records a program for
controlling an image processing apparatus by a
computer, wherein the program causes the computer to

convert an input image into a first image to which an
image quality adjustment process was executed on the
basis of a stored image quality adjustment value before
performing an image quality adjustment operation, and
5 into a second image to which an image quality
adjustment process was executed on the basis of an
image quality adjustment value of newly performing an
adjustment operation; and execute a trimming process to
parts of the converted first and second images to
10 display obtained image pieces on one screen with
arranged state.

To achieve the above object, the invention
according to an eighth aspect is characterized by a
recording medium which records a program for
15 controlling an image processing apparatus by a
computer, wherein the program causes the computer to
execute an image quality adjustment process to an input
image on the basis of a stored image quality adjustment
value before performing an image quality adjustment
20 operation and convert the input image into a first
image which was reduced, and execute an image quality
adjustment process to the input image on the basis of
an image quality adjustment value of newly performing
an adjustment operation and convert the input image
25 into a second image which was reduced; and display the
converted first and second images on one screen with
arranged state.

10042231.01102

To achieve the above object, the invention according to a ninth aspect is characterized by a recording medium which records a program for controlling an image processing apparatus by a computer, wherein the program causes the computer to execute an image quality adjustment process to an input image on the basis of a stored image quality adjustment value before performing an image quality adjustment operation and convert the input image into a first image which was reduced, and execute an image quality adjustment process to the input image on the basis of an image quality adjustment value of newly performing an adjustment operation and convert the input image into a second image which was reduced; and execute a trimming process to each part of the converted first and second images to display obtained image pieces on one screen with arranged state.

Other functions and features of the invention will become apparent from the following embodiments based on the attached drawings.

BRIEF DESCRIPTION OF THE DRAWINGS

Fig. 1 is a block diagram showing the structure of an image processing apparatus in the first embodiment;

Fig. 2 is a schematic view of a displayed image in the first embodiment;

Fig. 3 is a flow chart showing a processing

procedure in the first embodiment;

Fig. 4 is a schematic view of a displayed image in the second embodiment;

Fig. 5 is a schematic view of a displayed image in the third embodiment;

Fig. 6 is a block diagram showing the structure of an image processing apparatus in the fourth embodiment; and

Fig. 7 is a schematic view of a displayed image in the fourth embodiment.

DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENTS

(First Embodiment)

Fig. 1 shows the structure of an image processing apparatus in the first embodiment to which the present invention is applied. In Fig. 1, numeral 1 denotes a resolution converter acts as an image enlargement and reduction means. Numeral 6 denotes an image input terminal for inputting a digital video signal. Numeral 21 and 22 respectively denote first and second image data operation blocks act as an image quality adjustment process means. Numeral 31 and 32 denote nonvolatile memories such as first and second EEPROM's (Electrically Erasable Programmable Read-Only Memories) or the like act as an image quality adjustment value storage means.

Numeral 4 denotes a screen synthesis block acts as

20110122001

a multiscreen synthesis means. Numeral 5 denotes a display used for displaying images. Numeral 71 and 72 denote first and second frame memories function as buffers for temporarily storing image data. Numeral 74
5 denotes an OSD signal generator for generating a signal of an OSD (On Screen Display) which visually displays various operation states or the like for an operator. Numeral 75 denotes an operation key block used for performing various operations by the operator. Numeral
10 76 denotes a CPU (Central Processing Unit) which controls the entire of the image processing apparatus and takes an interface with the operator.

The operation key block 75 detects various keys operations according to operations performed by the
15 operator and notifies related key data to the CPU 76. Upon receiving the data input, the CPU 76 controls the entire of an image display apparatus including the resolution converter 1, the first and second nonvolatile memories 31 and 32, the OSD signal
20 generator 74 and other circuit blocks (not shown).

Image data input from the image input terminal 6 is reduced to half the size of the original size in longitudinal and lateral directions by the resolution converter 1 and once stored in the frame memories 71
25 and 72. Subsequently, an operation process regarding an image quality adjustment is executed to the reduced image data output from the frame memories 71 and 72 on

2025 RELEASE UNDER E.O. 14176

the basis of image quality adjustment values stored in the first and second nonvolatile memories 31 and 32 in the first and second image data operation blocks 21 and 22. As the image quality adjustment values, for
5 example, various values such as lightness, contrast, chromaticity, hue, RGB (red, green and blue) balance, color temperature, gamma characteristics, sharpness (emphasis) and the like or combinations of these values correspond to the image quality adjustment value.

10 The image quality adjustment value just before starting an image quality adjustment operation is stored in the first nonvolatile memory 31 and the image quality adjustment value in performing the image quality adjustment operation by the operation key block
15 75 is stored in the second nonvolatile memory 32 by an instruction from the CPU 76.

The screen synthesis block 4 arranges the image data from the image data operation block 21 on a central position in a left half area in a display
20 screen, the image data from the image data operation block 22 on a central position in a right half area in the display screen and superimposes a signal from the OSD signal generator 74 on a central lower portion in the display screen, then the display 5 forms images to
25 which a multiscreen synthesis process was executed.

Fig. 2 schematically illustrates the display screen of the display 5 at this time of the above

state. In Fig. 2, numeral 101 denotes an image just before starting the image quality adjustment operation, numeral 102 denotes an image in performing the image quality adjustment operation and numeral 111 denotes an image quality adjustment display according to the OSD signal generator 74.

In this case, state of performing an adjustment operation of "lightness" to the image 102 displayed on a right side in the screen while comparing it with the image 101 just before starting the image quality adjustment operation displayed on a left side in the screen is indicated. It should be noted that the reason for giving an adjustment of the "lightness" as an example depends on a fact that the purpose of the present invention has to be illustrated more comprehensible in this description of expressing images in monochrome, and the adjustment is not limited to the lightness. For example, operations of various image quality adjustments such as contrast, chromaticity, hue, RGB balance, color temperature, gamma characteristics, sharpness (emphasis) and the like can be performed.

Next, a sequence (processing procedure) of the CPU 76 related to the image quality adjustment will be explained. A flow chart shown in Fig. 3 schematically shows a flow when the CPU 76 performs the image quality adjustment operation.

At first, after starting the flow in a step 201,
when the operator selects an image quality adjustment
mode using the operation key block 75, it is shifted to
a multiscreen display mode as shown in Fig. 2 in a step
5 202.

Then, a display process based on the OSD is
executed in a step 203, an image quality adjustment
value update process of the second nonvolatile memory
32 is executed in accordance with an instruction from
10 the operation key block 75 in a step 204 and a checking
process of an image quality adjustment mode terminating
instruction from the operation key block 75 is executed
in a step 205. If the image quality adjustment mode
terminating instruction does not exist, the flow
15 returns to the step 203 and the above processes are
repeated.

In the step 205, if the image quality adjustment
mode terminating instruction exists, the flow advances
to a step 206, where an image quality adjustment value
20 stored in the second nonvolatile memory 32 at that time
is firstly copied (mapping) to the first nonvolatile
memory 31. Then, in a next step 207, the flow is
returned to the display mode which is just before the
multiscreen display mode shifted in the step 202 and
25 the display according to the OSD signal generator 74 is
terminated to exit from a series of the image quality
adjustment sequence in a step 208.

2025 RELEASE UNDER E.O. 14176

Thus, according to the first embodiment, since the image quality adjustment operation can be performed while comparing the image to be adjusted with the image just before starting the image quality adjustment operation by displaying the image just before starting the image quality adjustment operation and the image to be adjusted, the adjustment operation can be easily performed.

(Second Embodiment)

Fig. 4 schematically illustrates a display screen of a display 5 in the second embodiment to which the present invention is applied. In Fig. 4, numeral 101 denotes an image just before starting the image quality adjustment operation, numeral 102 denotes an image in performing the image quality adjustment operation and numeral 111 denotes an image quality adjustment display according to an OSD signal generator 74. That is, the same reference numerals as those in the first embodiment are given. It should be noted that since circuit blocks for realizing the second embodiment are the same as those in the first embodiment shown in Fig. 1, the detailed description thereof will be omitted.

In the second embodiment, a reduction ratio in a resolution converter 1 is set $2/3$, and both sides of two images are cut out by a screen synthesis block 4, then a trimming process is executed to form images.

The trimming process of cutting out both sides of

the two images may be executed at the time of executing a reduction process in the resolution converter 1 or writing image data to first and second frame memories 71 and 72.

5 Thus, according to the second embodiment, when the image 101 just before starting the image quality adjustment operation and the image 102 to be adjusted are displayed, an image to which the adjustment operation can be easily performed for a user is
10 extracted by executing the trimming process to the image, then the adjustment operation can be performed using the image, therefore, the adjustment operation can be easily performed. The image to which the adjustment operation can be easily performed for the
15 user is such an image as found in a skin color portion of a human face or the like, for example, in a case where lightness is adjusted.

(Third Embodiment)

Fig. 5 schematically illustrates a display screen
20 of a display 5 in the third embodiment to which the present invention is applied. In Fig. 5, numeral 101 denotes an image just before starting the image quality adjustment operation, numeral 102 denotes an image in performing the image quality adjustment operation and
25 numeral 111 denotes an image quality adjustment display according to an OSD signal generator 74. That is, the same reference numerals as those in the first

embodiment are given. It should be noted that since circuit blocks for realizing the third embodiment are the same as those in the first embodiment shown in Fig. 1, the detailed description thereof will be omitted.

5 In the third embodiment, a reduction process in a resolution converter 1 is not executed and both sides of two images are cut out by a screen synthesis block 4, then a trimming process is executed to form images. The image quality adjustment display 111 according to
10 the OSD signal generator 74 is superimposed and synthesized on the lowest position in the image 102 in performing the image quality adjustment operation.

The trimming process of cutting out both sides of the two images may be executed at the time of executing
15 a reduction process in the resolution converter 1 or writing image data to first and second frame memories 71 and 72.

Thus, in the third embodiment, similar to the above-mentioned second embodiment, an image to which
20 the adjustment operation can be easily performed for a user is extracted, then the adjustment operation can be performed using the image, therefore, the adjustment operation can be easily performed.

(Fourth Embodiment)

25 Fig. 6 shows the structure of an image processing apparatus for realizing the fourth embodiment to which the present invention is applied. In the structure

shown in Fig. 6, a third image data operation block 23
acts as an image quality adjustment process means, a
third nonvolatile memory 33 acts as an image quality
adjustment value storage means and a third buffer
5 (frame memory) 73 for temporarily storing image data
are respectively added to the circuit structure shown
in Fig. 1 in the first embodiment so as to provide
three systems in total. Since the functions of each of
the blocks are same as those shown in Fig. 1 in the
10 first embodiment, the detailed description thereof will
be omitted.

The third nonvolatile memory 33 which is newly
added stores a default value previously set when the
image processing apparatus was shipped or forwarded.
15 In the ordinary operating state, a CPU 76 can not
update this default value.

In the fourth embodiment, a reduction ratio in a
resolution converter 1 is set $1/2$, and the image data
from a first image data operation block 21 is arranged
20 on a right upper position in a display screen by a
screen synthesis block 4, the image data from a second
image data operation block 22 is arranged on a right
lower position in the display screen and the image data
from the third image data operation block 23 is
25 arranged on a left upper position in the display screen
respectively, and a signal from an OSD signal generator
74 is superimposed on a left lower position in the

20110101 10:00:00

display screen, then a display 5 forms the image to which a multiscreen synthesis process was executed.

Fig. 7 schematically illustrates the display screen of the display 5 at this time of the above-mentioned state. In Fig. 7, numeral 101 denotes an image just before starting the image quality adjustment operation, numeral 102 denotes an image in performing the image quality adjustment operation and numeral 111 denotes an image quality adjustment display according to the OSD signal generator 74. That is, the same reference numerals as those in the first embodiment are given. In Fig. 7, numeral 100 denotes an image to which an image adjustment process was executed on the basis of the default value of the image quality adjustment value stored in the third nonvolatile memory 33.

Therefore, the standard image 100 based on the image quality adjustment default value is displayed on a left upper position in the display screen and the image 101 just before starting the image quality adjustment operation is displayed on a right upper position in the display screen, and an operator performs an image quality adjustment operation to the image 102 displayed on a right lower position in the screen while comparing it with the above-mentioned images.

Thus, according to the fourth embodiment, an

adjustment operation of the image can be performed while comparing the standard image of the image quality adjustment default value with the image just before starting the image quality adjustment operation by displaying the standard image of the image quality adjustment default value, the image just before starting the image quality adjustment operation and the image to be adjusted with arranged state, therefore, the adjustment operation can be easily performed.

10 (Other Embodiments)

In the above first to fourth embodiments according to the present invention, the image data operation blocks 21, 22 and 23 were provided on the following stages of the resolution converter 1. However, mutual positions between the image data operation blocks and the resolution converter 1 may be replaced, and image data to which the image quality adjustment processes were executed by those image data operation blocks may be respectively reduced by exclusive resolution converters.

Further, image data operation blocks capable of executing adjustment processes using an individual image quality adjustment value every area in a screen are provided on the following stages of a multiscreen synthesis means as an image quality adjustment process means, and the image quality adjustment process may be executed for one image which is multiscreen synthesized

by a screen synthesis block.

In the first to third embodiment according to the present invention, the image 101 just before starting the image quality adjustment operation and the image 102 in performing the image quality adjustment operation were displayed with arranged state. However, the standard image 100 of the image quality adjustment default value as explained in the fourth embodiment may be displayed instead of the image 101 just before starting the image quality adjustment operation.

Further, a method of selecting any one image from the standard image 100 of the image quality adjustment default value or the image 101 just before starting the image quality adjustment operation by an operator and displaying the selected one image as a reference image is also considered.

In any of the above-mentioned embodiments according to the present invention, the arrangement of the reference image and the image 102 in performing the image quality adjustment operation is not limited to the arrangements as shown in Figs. 2, 4, 5 and 7, and a reduction ratio for the both images and the trimming quantity may be changed.

In any of the above-mentioned embodiments according to the present invention, a digital video signal is used as an input image signal. However, it is needless to say that an effect of the present

invention does not change in a case where the
adjustment process is executed after an analog video
signal is A/D (analog-to-digital) converted or an
analog process is executed to the image quality
5 adjustment process means itself.

The present invention is applicable to a system
composed of plural equipments (e.g., a host computer,
an interface equipment, a reader, a printer, and the
like) or to an apparatus including a single equipment
10 (e.g., a digital TV receiver, a video camera, a video
editing apparatus, and the like).

It is needless to say that an object of the
present invention can be achieved in a case where a
recording medium (storage medium) recording the program
15 codes of a software for realizing the functions of the
above-mentioned embodiments is supplied to a system or
an apparatus and then a computer (or CPU or MPU) in the
system or the apparatus reads and executes the program
codes stored in the recording medium.

20 In this case, the program codes themselves read
from the recording medium realize the functions of the
above-mentioned embodiments, and the recording medium
recording such the program codes constitutes the
present invention.

25 The recording medium recording the program codes
and conversion data such as a table or the like can be,
for example, an FD (Floppy Disk), a hard disk, an

optical disk, a magnetooptical disk, a CD-ROM (Compact Disk Read-Only Memory), a CD-R (Compact Disk Recordable), a magnetic tape, a nonvolatile memory card (IC (Integrated Circuit) card), a ROM or the like.

5 It is needless to say that the present invention also includes not only a case where the functions of the above-mentioned embodiments are realized by the execution of the program codes read by the computer, but also a case where an OS (Operating System) or the
10 like functioning on the computer executes all the process or a part thereof according to the instructions of the program codes, thereby realizing the functions of the above-mentioned embodiments by the executed processes.

15 As explained above, since an input image is reduced and an image in performing the image adjustment operation is to be displayed arranged with a standard image or an image before performing an adjustment operation treated as a reference image, an effect that
20 difference in the adjustment can be easily recognized and a delicate image quality adjustment operation can be easily performed is obtained.

20110722-01